

Kaze Plus Tech Data

DESCRIPTION	UNIT	KAZE PLUS				
Details						
Tonnage Class	TR	1.0TR	1.0TR	1.5TR	1.5TR	2.0TR
Star Rating		5	3	3	5	2
Model Number		RAW511HEDO	RAW312HEDO	RAW318HFDO	RAW518HEDO	RAW222KVD
Compressor	Type	ROTARY-R32	ROTARY-R32	ROTARY-R32	ROTARY-R32	ROTARY-R22
Performance						
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1
Rated Capacity - Cooling/Heating	BTU/Hr	12000	11260	17402	18000	21019
Rated Capacity - Cooling/Heating ISEER	Watts	3517	3300	5100	5275	6160
Annual Power Consumption (As per BEE Normms)	Kwh	789.14	851.52	1277.28	1134.28	1734.00
Fan Speed	Steps	3	3	3	3	3
Sound Level*	dB	50	46	50	50	52
Air Flow (Super High) - Cooling / Heating	CFM	400	295	450	450	470
Electrical						
Rated Power Input - Cooling/Heating	Watts	1019	1100	1650	1465	2240
Current Drawn - Cooling / Heating	Amps	4.7	4.9	7.55	6.7	9.9
Advanced Features						
Remocon	Type	Wireless	Wireless	Wireless	Wireless	Wireless
Kaimin						
Filter Clean Indicator		✓		✓	✓	✓
On/Off Timer with Advance Start Up		✓	✓	✓	✓	✓
Auto Power Save Mode		✓		✓	✓	✓
Wireless LCD Remote with Backlight		✓	✓	✓	✓	✓
Key Features						
Kaimin - Cooling & Heating						
Defrosting Sensor						
Auto Restart		✓	✓	✓	✓	✓
Digi Lock			✓			
Auto Fan Speed		✓	✓	✓	✓	✓
Silent Mode		✓		✓	✓	✓
Auto Climate Technology						
Precoated Alluminum Fins		✓		✓	✓	✓
Dimensions						
Dimension (WXHXD)	mm	660 X 430 X 755	560X377X615	660 X 430 X 755	660 X 430 X 755	660 X 430 X 755
Net Weight	Kg	52	40	60	62	64

Notes:

Features may vary from model to model.

*At Super Silent fan speed & at a distance of 1 m.

Hitachi Air Conditioners are designed to work in ambient temperature up to 52°C.

Due to continuous research & development, specifications, features and look may change without prior notice.