

Shizuka Tech Data

DESCRIPTION	UNIT	SHIZUKA INVERTER SERIES	
Details			
Tonnage Class	TR	1.5TR	1.5TR
Star Rating		5	3
Model Number		RAW518HFEOZ1	RAW318HFEOZ1
Compressor	Type	Twin Rotary-R32	Twin Rotary-R32
Performance			
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1
Rated Capacity - Cooling/Heating	BTU/Hr	17400	17400
Rated Capacity - Cooling/Heating	Watts	5100	5100
Maximum Cooling Capacity	BTU/Hr	19450	18930
Maximum Cooling Capacity	Watts	5700	5550
ISEER		3.35	3.09
Annual Power Consumption (As per BEE Norms)	Kwh	1179.68	1279.15
Fan Speed	Steps	3	3
Sound Level*	dB	50	50
Air Flow (Super High) - Cooling / Heating	CFM	450	450
Electrical			
Rated Power Input - Cooling/Heating	Watts	1749	1890
Current Drawn - Cooling / Heating	Amps	8.0	8.65
Advanced Features			
Remocon	Type	Wireless	Wireless
Expandable Inverter		✓	✓
Filter Clean Indicator		✓	✓
Auto Power Save Mode		✓	✓
Wireless LCD Remote with Backlight		✓	✓
Key Features			
Defrosting Sensor		✓	✓
Auto Restart		✓	✓
Auto Fan Speed		✓	✓
Precoated Alluminum Fins		✓	✓
Dimensions			
Dimension (WXHXD)	mm	660 X 430 X 755	660 X 430 X 755
Net Weight	Kg	52.5	50.5

Notes:

Features may vary from model to model.

*At Super Silent fan speed & at a distance of 1 m.

Hitachi Air Conditioners are designed to work in ambient temperature up to 52°C.

Due to continuous research & development, specifications, features and look may change without prior notice.