## **Kiyora** Tech Data

## Kiyora 5200FX Kiyora 4200FX

DESCRIPTION	UNIT	KIYORA 5200FX	KIYORA 5200FX	KIYORA 4200FX
Details				
X Series		X Series	X Series	X Series
Model Number		RAPG512FFEO	RSRG518FFEO	RMRG422FFEO
onnage	TR	1.0	1.5	1.8
Compressor	Type /	Tropical Rotary / R32	Tropical Rotary / R32	Tropical Twin Rotary /
·	Refrigerant	riopical notary / noz	Tropical Notary / NO2	R32
Performance				
tated Cooling (100 % load)	BTU/Hr (Watts)	12000 (3516)	17897 (5245)	21500 (6300)
laximum Cooling	BTU/Hr (Watts)	12600 (3700)	19000 (5568)	23200 (6800)
ated ISEER	4	5.2	5.20	4.50
nnual Power Consumption As per BEE Norrms)	(kWh)	523.15	780.60	1084.82
an Speed	No. of steps	5	5	5
ir Flow (IDU) (Cooling-Super igh)	CFM	425	620	620
ound level *1	db	32	34	37
lectrical				
ated Power Supply	Volts / Hz /	230/50/1	230/50/1	230/50/1
FFV	Phase			11 <del>-</del>
ated Power Input	Watts	870	1330	1820
ated Current Drawn	Amps	3.98	6.37	8.30
esthetic				
conic Wave		✓	✓	✓
mbience Light		✓	✓	✓
ir Technology				
Vave Blade /Big flow		✓	✓	✓
eflecter/Auto Coil Dry				
Fresh (FrostWash echnology)		✓	✓	✓
-				
Advanced Features Expandable				<b>✓</b>
		•	•	<b>∨</b> ✓
ropical Inverter		•	<b>v</b>	v •
00% Cooling at 43° C		•	•	•
00% Inner Grooved Copper ubes		•	•	•
uperslit Fins*2		./	./	./
		•	•	•
tabilizer Free Operation		· /	· /	·
ilter clean indicator		·	· .	· /
Penta Sensor Stainless Steel Coated Filter		v	<b>v</b>	<b>v</b>
Superfine Mesh filter		✓	•	•
(ey Features				
On / Off Timer		<b>✓</b>	<b>✓</b>	✓
Hydrophilic Fins (Indoor Unit)		✓	✓	✓
One Touch Super Silent		✓	✓	✓
Backlight Remote controller		✓	✓	✓
ssurance				
Compressor Warranty	1 + 9 Years	✓	✓	✓
Controller (PCB) Warranty	1 + 4 Years	✓	✓	✓
Varranty on Entire Machine	1 Years	✓	✓	✓
imensions				
imension (IDU) (WXHXD)	mm	798 X 295 X 239	997 X 294 X 253	997 X 294 X 253
imension (ODU) (WXHXD)	mm	658 X 530 X 274	750 X 548 X 288	792 X 600 X 299
uction Line Diameter	mm (Inches)	9.53 (3/8")	12.7 (1/2")	15.88 (5/8")
iquid Line Diameter	mm (Inches)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")

Notes:

Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model. \*At Super Silent fan speed & at a distance of 1 m. Permissible maximum pipe length limit is up to 25 mtrs. Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice. #T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.