	DESCRIPTION		
	Model Name	iZen 3500FWXL	iZen 3500FWXL
	Model Number	RAS.V318PCAISH	RAS.V312PCAISH
	Tonnage TR	1.5	1.0
	Star Rating	3	3
	Compressor Type / Refrigerant	Rotary / R32	Rotary / R32
	Rated Cooling (100 BTU/Hr (Watts) % load)	17710 (5190)	11800 (3458)
	Maximum Cooling BTU/Hr (Watts)	18700 (5480)	12600 (3692)
	Rated ISEER	3.92	4.00
	Annual Power <sup>(kWh)</sup> Consumption (As per BEE Norrms)	1024.34	669.16
	Fan Speed No. of steps	5	5
Performance	Air Flow (IDU) CFM (Cooling-Super High)	530	406
Perfo	Sound level *1 dbA	34	32
	Rated Power Volts / Hz / Supply Phase	230 / 50 / 1	230 / 50 / 1
e	Rated Power Input Watts	1940	1095
Electrical	Rated Current Amps Drawn	8.88	5.00
	ice Clean (Frost wash)	<u>√</u>	√
	Surround Cooling *2 (Long Air throw)	V	v
S.	Ambience Light	V	V
Key Features	Odour free air (Soft Dry)	٧	V
Key F	Silent air	٧	<u>√</u>
	AQ-tiv Ion (Ionizer) airCloud Home -Wifi Enabled		
	4 Way Air Swing	V	V
	Hexa Sensor		
	My Mode	V	V
	Powerful Mode	V	V
	One Touch Super Silent	V V	V V
	ECO Mode (Sensorless)	v V	v V
	Good Sleep / Sleep mode	√ √	v √
	On / Off Timer	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·
tures	Real Time Clock/ On/Off timer (24		
Ad van ced Features	hours) Tropical Design	V	V
lvance	100% Inner Grooved Copper Tubes	V	V
A	Superslit Fins	٧	v
	Filter clean indicator	V	V
	Superfine Mesh filter	V	V
	Up/Down Swing	٧	v
	Stabilizer Free Operation	٧	V
Assurance	Hydrophilic Fins (Indoor Unit)	٧	V
	Backlight Remote controller	<u>√</u>	√ 
	Compressor 1 + 9 Years Warranty	<u>۷</u>	<u>√</u>
	Controller (PCB) 1 + 4 Years Warranty	V	v
	Warranty on Entire 1 Year Machine Compressor 1 + 4 Years Warranty	V	v
	Warranty Dimension (IDU) mm (WXHXD)	950 X 294 X 235	780 X 280 X 227
	Dimension (ODU) mm (WXHXD)	750 X 550 X 290	658 X 530 X 274
	Suction Line mm (Inches) Diameter	12.7(1/2")	9.52(3/8")
**		r	•

7.8/24.4

	DESCRIPTION	
	Model Name	iZen 3500FWXL
	Model Number	RAS.V322PCAISH
	Tonnage TR	1.8
	Star Rating	3
	Compressor Type / Refrigerant	Twin Rotary / R32
	Rated Cooling (100 BTU/Hr (Watts) % load)	21500 (6300)
	Maximum Cooling BTU/Hr (Watts)	23000 (6740)
	Rated ISEER	3.90
Performance	Annual Power (kWh)	
	Consumption (As per BEE Norrms)	1251.00
Per	Fan Speed No. of steps	5
	Air Flow (IDU) CFM	
	(Cooling-Super High)	530
	Sound level *1 dbA	37
a	Rated Power Volts / Hz / Phase Supply	230 / 50 / 1
Electrical	Rated Power Input Watts	2020
ш —	Rated Current Amps Drawn	9.24
	ice Clean (FrostWash)	√
	Surround Cooling *2 (Long Air throw)	√
Ň	Ambience Light	v
ature	Odour free air (Soft Dry)	V
Key Features	Silent air	V
-	AQ-tiv lon (lonizer)	
	airCloud Home -Wifi Enabled	V
	4 Way Air Swing	
	Hexa Sensor	٧
	My Mode	<u>√</u>
	Powerful Mode	٧
	One Touch Super Silent ECO Mode (Sensorless)	V
	Good Sleep / Sleep mode	٧
	On / Off Timer	V
res	Real Time Clock/ On/Off timer (24 hours)	٧
Advanced Features	Tropical Design	
anced	100% Inner Grooved Copper Tubes	V
Adva	Superslit Fins	v v
	- Filter clean indicator	v v
	Superfine Mesh filter	v v
	Up/Down Swing	· · · · · · · · · · · · · · · · · · ·
	Stabilizer Free Operation	 √
	Hydrophilic Fins (Indoor Unit)	√
	Backlight Remote controller	√
	Compressor 1+9 Years	√
e	Warranty Controller (PCB) 1+4 Years	
Assurance	Warranty	٧ 
Ass	Warranty on Entire 1 Year Machine	V
	Compressor 1 + 4 Years Warranty	
	Dimension (IDU) mm	950 X 294 X 235
	(WXHXD)	
sions	Dimension (ODU) (WITA) (WXHXD)	800 x 640 x 298
Dimensions	Suction Line mm (Inches)	15.8(5/8")
Dir	Diameter	( )

Liquid Line mm (Inches) Diameter	6.35(1/4")
Net Weight IDU Kg /ODU	10/34.7
Notes:     Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.     *1 At Super Silent fan speed & at a distance of 1 m.     *2 Air flow range for surround cooling will vary as per chassis/ tonnage.     Permissible maximum pipe length limit is up to 25 mtrs     Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.     *1&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.	

	DESCRIPTION	
	Model Name	iZen 3500FWXL
	Model Number	RAS.V324PCAISH
	Tonnage TR	2.0
	Star Rating	3
	Compressor Type / Refrigerant	Twin Rotary / R32
	Rated Cooling (100 % load) BTU/Hr (Watts)	23715 (6950)
	Maximum Cooling BTU/Hr (Watts)	25080 (7350)
	Rated ISEER	3.85
Performance	(kWh) Annual Power Consumption (As per BEE Norrms)	1397.61
č	Fan Speed No. of steps	5
	Air Flow (IDU) (Cooling-Super CFM High)	635
	Sound level *1 dbA	37
a	Rated Power Supply Volts / Hz / Phase	230 / 50 / 1
Electrical	Rated Power Input Watts	2450
<b></b>	Rated Current Drawn Amps	11.21
	ice Clean (FrostWash)	√
	Surround Cooling *2 (Long Air throw)	√
w	Ambience Light	٧
ature	Odour free air (Soft Dry)	V
Key Features	Silent air	v
	AQ-tiv Ion (Ionizer)	
	airCloud Home -Wifi Enabled	٧
	4 Way Air Swing	
	Hexa Sensor	√
	My Mode	٧
	Powerful Mode One Touch Super Silent	٧
	ECO Mode (Sensorless)	٧
	Good Sleep / Sleep mode	V
w	On / Off Timer	V
ature	Real Time Clock/ On/Off timer (24 hours)	V
Ced Fe	Tropical Design	√
Advanced Features	100% Inner Grooved Copper Tubes	V V
	Superslit Fins	√
	Filter clean indicator	- ۷
	Up/Down Swing	٧
	Stabilizer Free Operation	v
	Hydrophilic Fins (Indoor Unit)	٧
	Backlight Remote controller	V
	Compressor Warranty 1 + 9 Years	٧
Assurance	1 + 4 Years Controller (PCB) Warranty	v
	Warranty on Entire Machine 1 Year	٧
	Compressor Warranty 1+4 Years	
	mm Dimension (IDU) (WXHXD)	1050 X 294 X 255
Dimensions	mm Dimension (ODU) (WXHXD)	800 x 640 x 298
Dime	Suction Line Diameter mm (Inches)	15.8(5/8")
	Liquid Line Diameter mm (Inches)	6.35(1/4")

Net Weight IDU /O	NU Kg	11.4/34.7
Notes:   Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control,   Auto Fan Speed, Auto Restart, Green Refrigerant, 43 Quality Test features are available in every model.   *1 At Super Silent fan speed & at a distance of 1 m.   *2 Air flow range for surround cooling will vary as per chassis/ tonnage.   Permissible maximum pipe length limit is up to 25 mtrs   Features may vary from model to model. Due to continuous research & development,   specifications & features may change without prior notice.   *T&C apply. Offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.		