

Model Name			iZen 3500SWXL	
	Description	Unit		
Details	Model Number		RAS.V318PCBISH	RAS.V322PCBISH
	Star Rating		3	3
	Compressor	Type / Refrigerant	Rotary / R32	Twin Rotary / R32
Performance	Rated Cooling (100 % load)	BTU/Hr (Watts)	17060 (5000)	21500 (6300)
	Maximum Cooling	BTU/Hr (Watts)	18084 (5300)	23000 (6740)
	Rated ISEER		3.82	3.82
	Annual Power Consumption (As per BEE Norms) (kWh)		1012.62	1277.22
	Fan Speed	No. of steps	5	5
	Air Flow (IDU) (Cooling-Super High)	CFM	530	530
	Sound level *1	dbA	34	37
Electrical	Rated Power Supply	Volts / Hz / Phase	230 / 50 / 1	230 / 50 / 1
	Rated Power Input	Watts	1940	2235
	Rated Current Drawn	Amps	8.8	10.23
Key Features	Bigger IDU - 1050 mm			
	Dual Louver			
	Ice Clean (FrostWash)		✓	✓
	AQ-tiv Ion (Ionizer)			
	airCloud Home -Wifi Enabled		✓	✓
	4 Way Swing		✓	✓
	Xpandable		✓	✓
	Long air throw *2		✓	✓
	Ambience Light			
	Odour-free air (Soft Dry)		✓	✓
Remote Features	Silent air (Wave Blade Design)		✓	✓
	My Mode		✓	✓
	Backlight Remote controller		✓	✓
	Powerful Mode		✓	✓
	One Touch Super Silent		✓	✓
	ECO Mode		✓	✓
	Good Sleep mode		✓	✓
	On / Off Timer		✓	✓
Advance Features	Real Time Clock/ On/Off timer (24 hours)		✓	✓
	Hexa Sensor		✓	✓
	Tropical Design up to 52 °C		✓	✓
	100% Inner Grooved Copper Tubes		✓	✓
	SuperSlit Fins		✓	✓
	Filter clean indicator		✓	✓
	Anti-bacterial SuperFine Mesh filter		✓	✓
	Up/Down Swing		✓	✓
Assurance [†]	Stabilizer Free Operation		✓	✓
	Hydrophilic Fins (Indoor Unit)		✓	✓
	Compressor Warranty	1 + 9 Years	✓	✓
Dimensions	Controller (PCB) Warranty	1 + 4 Years	✓	✓
	Warranty on Entire Machine	1 Year	✓	✓
	Dimension (IDU) (W x H x D)	mm	950 x 294 x 235	950 x 294 x 235
	Dimension (ODU) (W x H x D)	mm	750 x 550 x 290	800 x 640 x 298
	Suction Line Diameter	mm (Inches)	12.7(1/2")	12.7(1/2")
Liquid Line Diameter	mm (Inches)	6.35(1/4")	6.35(1/4")	
Net Weight IDU/ODU	Kg	10.0/27.4	9.6/32.9	

Notes:
 Unit performance conforms to IS1391-2
 Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart and Green Refrigerant features are available in every model.
 *1 At Super Silent fan speed & at a distance of 1 m.
 *2 Air flow range for long air throw will vary as per chassis/tonnage, 24 m. in 1050 mm, 18 m. in 950 mm & 12 m. in 780 mm in fan mode.
 The permissible maximum pipe length limit is up to 25 m.
 Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.
 †T.C. apply, offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.
 *It indicates that unit has 12 hour On/Off timer. **It indicates that the model had Peta Sensors.