

Model Name			iZen 3400SXL		
	Description	Unit			
Details	Model Number		RAS.G318PCBISS	RAS.G322PCBISS	RAS.G324PCBISS
	Star Rating		3	3	3
	Compressor	Type / Refrigerant	Rotary / R32	Twin Rotary / R32	Twin Rotary / R32
Performance	Rated Cooling (100 % load)	BTU/Hr (Watts)	17060 (5000)	21500 (6300)	23715 (6950)
	Maximum Cooling	BTU/Hr (Watts)	18084 (5300)	23000 (6740)	25080 (7350)
	Rated ISEER		3.82	3.82	3.82
	Annual Power Consumption (As per BEE Norms)	(kWh)	1012.62	1277.22	1409.41
	Fan Speed	No. of steps	5	5	5
	Air Flow (IDU) (Cooling-Super High)	CFM	530	530	635
	Sound level *1	dbA	34	37	37
Electrical	Rated Power Supply	Volts / Hz / Phase	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1
	Rated Power Input	Watts	1940	2235	2480
	Rated Current Drawn	Amps	8.8	10.23	11.35
Key Features	Bigger IDU - 1050 mm				√
	Dual Louver				
	Ice Clean (FrostWash)		√	√	√
	AQ-tiv Ion (Ionizer)				
	airCloud Home - Wifi Enabled				
	4 Way Swing		√	√	√
	Xpandable		√	√	√
	Long air throw *2		√	√	√
	Ambience Light				
	Odour-free air (Soft Dry)		√	√	√
	Silent air (Wave Blade Design)		√	√	√
Remote Features	My Mode		√	√	√
	Backlight Remote controller		√	√	√
	Powerful Mode		√	√	√
	One Touch Super Silent		√	√	√
	ECO Mode		√	√	√
	Good Sleep mode		√	√	√
	On / Off Timer		√	√	√
	Real Time Clock/ On/Off timer (24 hours)		√	√	√
Advance Features	Hexa Sensor		√	√	√
	Tropical Design up to 52 °C		√	√	√
	100% Inner Grooved Copper Tubes		√	√	√
	SuperSlit Fins		√	√	√
	Filter clean indicator		√	√	√
	Anti-bacterial SuperFine Mesh filter		√	√	√
	Up/Down Swing		√	√	√
	Stabilizer Free Operation		√	√	√
	Hydrophilic Fins (Indoor Unit)		√	√	√
Assurance [®]	Compressor Warranty	1 + 9 Years	√	√	√
	Controller (PCB) Warranty	1 + 4 Years	√	√	√
	Warranty on Entire Machine	1 Year	√	√	√
Dimensions	Dimension (IDU) (W x H x D)	mm	950 x 294 x 235	950 x 294 x 235	1050 X 294 X 255
	Dimension (ODU) (W x H x D)	mm	750 x 50 x 290	800 x 640 x 298	800 x 640 x 298
	Suction Line Diameter	mm (Inches)	12.7(1/2")	12.7(1/2")	15.8(5/8")
	Liquid Line Diameter	mm (Inches)	6.35(1/4")	6.35(1/4")	6.35(1/4")
	Net Weight IDU/ODU	Kg	10.0/27.4	9.6/32.9	11.4/34.7

Notes:
 Unit performance conforms to IS1391-2
 Auto Mode, Cool Mode, Fan Mode, Dry Mode (better humidity control), LCD Remote Control, Auto Fan Speed, Auto Restart and Green Refrigerant features are available in every model.
 *1 At Super Silent fan speed & at a distance of 1 m.
 *2 Air flow range for long air throw will vary as per chassis/tonnage, 24 m. in 1050 mm, 18 m. in 950 mm & 12 m. in 780 mm in fan mode.
 The permissible maximum pipe length limit is up to 25 m.
 Features may vary from model to model. Due to continuous research & development, specifications & features may change without prior notice.
 #1 & #2 apply, offer available on select models only and subject to company's discretion. Offer can be withdrawn anytime without prior notice.
 *It indicates that unit has 12 hour On/Off timer. **It indicates that the model had Peta Sensors.